

15.6" Ubiquitous Touch Computer UTC-115| with 11th Gen Intel® Core™ i5/i3 Processor



Features

- Slimmer and Lighter design
- Low power and fanless system design
- Built-in Intel® Core™ i5-1145G7E
- 15.6" monitor with 16:9 widescreen display
- IP65-rated front panel for water and dust resistance
- Clean back cover design with 3 Way IO cable routing
- Supports both landscape and portrait screen orientations
- VESA 100 mm standard mounting holes for varied mounting demands
- Support DeviceOn/iService software for remote device management













DeviceOn/iService

Introduction

UTC-115 features an all-in-one computing system which equipped with wide format, touch based LCD panel. It is easy to integrate key peripherals and display systems for diversified self-service and interactive signage deploy in different application areas.

Thanks for the slim and light looking with 3 way cable routing design, makes UTC-115 good fit to diverse scenarios and areas.

The systems deliver updated information with well-designed interactive interfaces, with fully ensure relevant content and targeted promotions are delivered. UTC series touch panel computers are the best investments to enhance user satisfaction, further brand equity, and maximize business profits.

Moreover, Advantech DeviceOn/iService Software is a next-generation unified device management unified device management solution based on the WISE-DeviceOn platform. With support for batch operations and multi-device control, DeviceOn/iService enables easy device configuration and deployment for convenient remote device management.


Specifications

	CPU	Intel Core i5-1145G7E (Default) Intel Core i3-1115G4E
	Base Frequency	i5: 1.50 GHz (Quad-Cores) i3: 2.20 GHz (Dual-Cores
	Memory	1 x 260pin SO-DIMM DDR4 3200 MHZ up to 32GB
	Storage	1 x 2.5 internal SATA storage*, M.2 2242/2280 SSD
	Network	2 x Gigabit Ethernet ports (Supports Wake on LAN)
Process system	I/O Ports	2 x RS-232 COM (COM2 RS-232/422/485) 3 x USB 3.2 Gen1 Type-A 1 x USB 3.2 Gen1 Type-C 1 x DC-in USB Type-C 2 x Gigabit Ethernet ports 1 x HDMI 1.4 1 x Audio Phone Jack
	Stereo Speaker	2 x 2W
	Bus expansion	1 x M.2 key2230, 1 x M.2 key2280
	Mounting	VESA 100 x 100 mm (Screw Size, M4, 6mm)
	Dimension (WxHxD)	398.8 x 248.2 x 29.5
	Weight	2.4kg
OS Support		Win 10 IoT Enterprise 64bit Linux
	Operating temperature	0 ~ 40 °C (32 ~ 104 °F)
	Relative Humidity	10 ~ 95% @ 40 °C non-condensing
Environment Specification	Vibration	0.5G
Liviloriment Specification	Shock	Shock 10G peak acceleration(11 msec. duration)
	Certification	CE, FCC, CB, UL, CCC, BSMI
	Front Panel Protection	IP 65 Compliant
	DC Input Rating	20V/4.5A (90W)
Power Supply	PoE	n/a
	Power consumption	35W
	Size/Type	15.6" FHD
	Max.Resolution	1920 x 1080
LCD Display	Max. Color	262K
LOD Display	Pixel Pitch (um)	179(H) x 179(V)
	Brightness (cd/m²)	300
	View Angle	170°/170°
	Туре	Projected Capacitive.
Touch Screen Option	Light Transmission	> 85%
T01.	Controller	USB Interface
TPM		TPM 2.0


Specifications (Cont.)


	Operating System	Windows 10
	Common Controls (Reboot, Shutdown)	✓
	Remote desktop	✓(VNC)
	Device-Specific Controls (Audio)	√ *
	Connection Status	✓
	Hardware Status	√ *
DeviceOn/iService Remote Device Management	Hard Disk Status	√*
	Batch Operation Support	✓
	OTA Storage Management	FTP
	OTA Software Updates	\checkmark
	Software Watchlist	✓
	Software Start/Stop	√ *
	Kiosk Mode	
*Dependent on device model	Peripherals Watchlist	√ *

Note: DeviceOn/iService software must be downloaded from the Advantech website at https://www.advantech.com/search/?q=DeviceOn%2FiService&st=support&sst=Utility Note: It will block some IO ports on the same side.



Fully- Integrated I/O





Ordering Information

For Worldwide Model

Part No.	Descriptions	
UTC-115IP-WWW1F	15.6" Pcap, FHD 1920x1080, I5-1145G7E CPU, 8G RAM, 128G SSD, Win 10 IOT, Wifi/BT, Silver Color	

Extra ordering information

Part No.	Descriptions
170203183C/170203183C-01	Power Cord UL 3P 10A 125V 183cm (EU)
1700001524	Power Cord EU 3P 2.5A 250V 183cm (US)
1700019146	Power Cord CCC 3P 2.5A 250V 183cm (China)
170203180A	Power Cord BSI 3P 2.5A 250V 183cm (UK)
1700025928-02	COM Port Converter cable RJ48-10P10C to D-SUB 9P 35cm
UTC-T01-STANDE	Tri Shape Floor Stand 120cm
UTC-100P-STAND0E	L Stand for UTC-115
UTC-300P-D20E	Desk Stand, Silver, for UTC-115/120
UTC-UPOS-STAND0E	Double Hinge Stand
UTC-AVALO-STAND0E	Avalo Stand
ARES-2423X-S151001	Table Stand for UTC-115 (Black)
ARES-2425X-S271001	Tilt Table Stand for UTC-100 Serires (Black) (Support Portrait & Landscape)
ARES-12250-L101000	Vesa Wall-mount for UTC-100 Series (Black)

Peripheral Mountable on All 4 Sides




Peripherals for UTC-100(AIO system) series

	Part No.	Description	
	UTC-100P-B11E	2D Barcode Scanner for UTC-115/120	
	UTC-100P-C10E	5M Camera for UTC-115/120	
	UTC-100P-R10E	RFID Scanner for UTC-115/120	
	UTC-100P-M10E	MSR Reader for UTC-115/120	
	UTC-100P-S10E	Smart Card Reader for UTC-115/120	
	UTC-100P-L10E	LED Light Bar for UTC-115/120	
	UTC-100P-F10E	Finger Print Reader for UTC-115/120	
	UTC-100P-T10E	Thermal Camera for UTC-115/120	

DeviceOn/iService

Unified Remote Device Management Software



Features

- Supports Advantech devices equipped with Windows, Android, and Linux OS
- Flexible device, location, user, and permissions management
- Enables remote monitoring and control of hardware, software, and peripherals
- · Supports over-the-air (OTA) firmware and software updates
- Ensures quick, easy, and secure device onboarding
- RESTful APIs for third-party system integration

Introduction

Advantech's DeviceOn/iService is a next-generation unified device management solution based on the WISE-DeviceOn platform. Designed to enable centralized monitoring and remote management, DeviceOn/iService supports Advantech devices equipped with Windows, Linux, or Android operating systems. The software also supports the management of applications and integrated peripherals, such as a barcode scanner, card reader, camera, and printer. Users can remotely access and control connected devices, take screenshots, rollout OTA upgrades, and use remote desktop capabilities for troubleshooting from any location at any time. Moreover, DeviceOn/iService supports batch operations to facilitate the management of multiple devices simultaneously for easy and convenient device configuration and deployment.

Total Management



Devices & Hardware

- Windows, Linux, Android
- Hardware, storage, battery

Remote Access



Failure notifications



Remote Controls

- Power controls
- Audio, backlight controls
- Software controls



OTA updates

Operational Efficiency

- System/software updates
- File repository management
- App store



Software & Peripherals

- Software monitoring & access
- Screens, USB devices, printers





Batch Controls

- 1-to-many batch reboot, etc.
- Time-saving tasks



Open for Expansion

- Peripheral integration
- Open APIs for integration



Troubleshooting

- Screenshots
- Remote desktop support



Setup Booster

- Software/peripheral watchlist
- Roles, rule templates

Note: Some functions may vary according to the product

System Architecture

